

Niche tiles®

Material Safety Data Sheet

IDENTITY BACKSPLASH TILE MURAL PREMIUM REAL METAL RESIN	PREMIUM REAL METAL / CAST METAL RESIN REAL BRONZE / REAL BRUSHED NICKEL / REAL RUST/ REAL ANTIQUE NICKEL / REAL POLISHED BRONZE / REAL COPPER / REAL WROUGHT IRON / REAL OIL RUBBED BRONZE / REAL BLACK BRONZE/ REAL PEWTER GRAPHITE
--	---

Section I - Manufacturer & Distributor Information

Manufacturer's Name GeremeYapı Malzemeleri San. ve Tic.A.Ş.	Telephone Number For Information and Emergency 678 709 6668
Address (Number, Street, City, State, Country and Postal Code) ITOB Organize Sanayi Bölgesi 10012 Sok. No:5 35477 Tekeli-Menderes-Izmir TURKEY	Date Prepared 06/02/2015
Distributor's Name GEREME ATLANTA INC.	Distributor's Telephone Number 678 709 6668

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	CAS Number	Concentration (%)	OSHA PEL (mg/m ³)	ACGIH (mg/m ³)	Other Limits Recommended
Metal Powders	7429-90-5	< 0.1 %	10 mg/m ³	Not established	
Calcium Carbonate	1317-65-3	15-30%	15mg/m ³	10 mg/ m ³	
Dolomite	16389-88-1	15-30%	15mg/m ³	10 mg/ m ³	

Section III - Physical/Chemical Characteristics

Boiling Point (Specify °F or °C)	not applicable	Specific Gravity (H ₂ O = 1)	0.85 – 1.00
Vapor Pressure (mm Hg.)	not applicable	Melting Point	> 2000 °F
Vapor Density (AIR = 1)	not applicable	Evaporation Rate	not applicable
Solubility In Water Insoluble	Appearance And Odor Insoluble Brittle solid; color may vary and Odorless		

Section IV - Fire and Explosion Hazard Data

Flash Point not applicable	Flammable Limits	LEL not applicable	UEL not applicable
Extinguishing Media None required. Non-flammable.			
Special Fire Fighting Procedures None required.			
Unusual Fire And Explosion Hazards None required.			

Section V - Reactivity Data

Unstable	not applicable	Conditions To Avoid Avoid contact with acids (e.g., acetic, hydrofluoric, etc.)
Stable	Stable in current form.	
Incompatibility (Materials To Avoid) Avoid contact with acids (e.g., acetic, hydrofluoric, etc.)		
Hazardous Decomposition Or Byproducts Under normal conditions these products do not release hazardous materials after installation.		
Hazardous Polymerization May Occur	not applicable	Conditions To Avoid
Hazardous Polymerization Will Not Occur	Will not occur	Not applicable

Section VI - Health Hazard Data

Route(s) Of Entry:	Inhalation: Yes	Skin: Yes	Ingestion: No
Health Hazards (Acute and Chronic) Acute - Excessive exposure to tile dust can cause eye, skin, and lung irritation from mechanical abrasion. Ingestion is not applicable for intact tile.			
Chronic - Not applicable for intact tiles. Excessive exposure to tile dust can cause discomfort and mechanical irritation. Long term exposure to silica dusts can lead to silicosis.			
Carcinogenicity:	NTP: Yes	IARC Monographs: Yes	OSHA Regulated: Yes
Signs And Symptoms Of Exposure Excessive exposure to tile dust can cause eye, skin, and lung irritation from mechanical abrasion. Long term exposure to silica dusts can lead to silicosis.			
Medical Conditions Generally Aggravated By Exposure Existing lung disease may be aggravated after exposure to tile dusts.			
Emergency And First Aid Procedures Skin: Wash dust off any affected area with soap and water. Inhalation: Remove the victim to fresh air if exposed to large amounts of tile cutting dust. Administer artificial respiration if breathing has stopped. Keep victim at rest. Call for prompt medical attention. Ingestion: Not applicable for intact tiles. * Have emergency eyewash station available in area where tiles are cut.			

Section VII - Precautions for Safe Handling and Use

Steps To Be Taken In Case Material Is Released Or Spilled Employ closed system and/or local exhaust ventilation. Use wet methods if needed to reduce generation of dust. Use respiratory protection in the absence of engineering controls.
Waste Disposal Method Waste should be disposed of in a landfill certified to accept such materials in accordance with federal, state, and local regulations.
Precautions To Be Taken In Handling And Storing Shelf life is unlimited. Do not store near acids. If tiles contact some acids, there is limited potential for leaching heavy metals.
Other Precautions Broken tile could be sharp; therefore, appropriate gloves should be worn if working with broken product.

Section VIII - Control Measures

Respiratory Protection (Specify Type) Tiles should be cut using wet or dry saw methods. Use of a properly fitted NIOSH/MSHA approved particulate respirator is recommended when cutting tiles dry.
Ventilation: Use adequate ventilation to keep exposure to dust below recommended exposure levels. Avoid inhaling dust. The highest probability of silica exposure occurs during dry cutting. Wet cutting methods are recommended.
Eye Protection: Use dust-proof goggles or safety glasses with side shields. Contact lenses may absorb irritants. Do not wear contact lenses in work areas.
Skin Protection: Cotton or leather work gloves should be worn when cutting this product to minimize skin exposure. Wash hands prior to eating drinking, or smoking, and at the end of the work shift, after cutting operations are conducted.
Other Protective Clothing or Equipment: Note: Personal protection information listed above is based upon general information as to normal uses and conditions. Where special or unusual uses or conditions exist, it is suggested that the expert assistance of an industrial hygienist or other qualified professional be sought.

Section VIII - Regulatory Section

Department of Transportation (DOT) Regulations Tile is not regulated by DOT.	
Toxic Substance Control Act (TSCA) This product and/or its components have been introduced into U.S. commerce and is listed in the Toxic Substance Control Act (TSCA) Inventory of Chemicals in Commerce. Hence, it is subject to all applicable provisions and restrictions under TSCA 40 CFR Section 721 and 723.250.	
Other information	
National Fire Protection Act Hazard Rating: Hazardous Material Information System Rating:	Health: 0 Fire: 0 Reactivity: 0 Health: 0 Fire: 0 Reactivity: 0